

Drinking Water Protection Section

PWSID# Month & Year Fluoridation & Nitrate or Nitrite P.O. Box 64975 **Removal Monthly Report** St. Paul, Minnesota 55164-0975 Name of Facility Entry Point Facility Name Fluoride Chemical Used: Fluoride Dilution: Raw Water Source(s) Raw Water Fluoride Concentration(s) Raw Water Nitrate or Nitrite Concentration(s): (Circle Nitrate or Nitrite) Well# Well# Well# Nitrate/Nitrite mg/L mg/L mg/LWell# Nitrate/Nitrite mg/L Operator Name (Print) Operator Contact Phone #: Signature Meter Fluoridation Analysis **Pumpage** Nitrate or Nitrite Analysis **Daily Fluoride** Reading Chemical (1000 gal.) **Tested Fluoride Distribution System Sample Entry Point Nitrate or Nitrite** Used (1000 gal.) Concentration **Point** Nitrogen (circle Nitrate or Nitrite) (gals./lbs) (mg/L) mg/L Day 1 2 3 4 5 6 1 2 3 4 5 6 7 8 9 **10** 11 12 13 14 15 16 **17** 18 19 20 21 22 23 24 25 **26** 27 28 29 **30** 31

INSTRUCTIONS FOR COMPLETING THE FLUORIDATION & NITRATE OR NITRITE REMOVAL MONTHLY REPORT

Column Number	
1	Daily water meter reading in thousands of gallons.
2	Pumpage in thousands of gallons: daily meter reading minus the previous day's meter reading.
3	The total number of gallons of fluoride solution used per day or the total pounds of fluoride compound used if you are using sodium silicofluoride.
4	Distribution system analysis results for fluoride monitoring samples. Daily sample collection is required. Do not collect and analyze composite samples.
5	Distribution system sample location for fluoride monitoring samples. Samples should be collected from different locations each day.
6	Entry Point (downstream of all treatment but prior to entry to distribution system) analysis results for nitrate or nitrite (measured as mg/L nitrogen) monitoring samples. Samples shall be collected and analyzed weekly . Daily monitoring is recommended if finished water concentrations are greater than 7.0 mg/L nitrate or 0.70 mg/L nitrite.

Notes: The raw water fluoride and nitrate or nitrate concentrations should be tested monthly.

The entry point nitrate or nitrite concentration must be tested weekly.

If any nitrate result is greater than 10 mg/L (as N), or any nitrite result is greater than 1.0 mg/L (as N), you should contact your **MDH District Engineer immediately**.

Test strips are not allowed to be used for these analyses.

Approved Nitrate and Nitrite compliance snalysis methods include:

Automated Cadmium Reduction Manual Cadmiun Reduction Ion Chromatography Capillary Ion Electrophoresis Automated Hydrazine Reduction (Nitrate)

Ion Selective Electrode (Nitrite) Spectrophotometric (Nitrite)

Comments:

Click here to enter text.

You may submit the Fluoridation & Nitrate or Nitrite Removal Monthly Report to the Minnesota Department of Health through these options:

Option 1 – Mail the report to:

Minnesota Department of Health Community Water Supply Unit P.O. Box 64975 St. Paul, MN 55164-0975

Option 2 – Email the report (as an attached file) to:

health.report-fluoride@state.mn.us.

The Fluoridation Monthly Reports and other forms can be found at Community Public Water Supply Forms (https://www.health.state.mn.us/communities/environment/water/com/com.html)